



- globe- and bellow seal valves, on/off valves
- electric/pneumatic/electro-pneumatic
- flange connection (DIN or ANSI)
- tri-clamp or threaded connection
- 2-way or 3-way
- high temperature and cryogenic application



SERIES

500



800



1000



- DN 15 ~ 100 (only DIN PN16)
- body in nodular cast iron
- internal parts in 316L
- soft seal
- pneumatic or electro-pneumatic
- medium: water, oil or steam

- DN 15 ~ 150
- DIN PN10-40 / ANSI 300
- 2-way or 3-way
- body in cast iron, cast steel or stainless steel
- pneumatic or electric

- DN 8 ~ 200
- all connections possible
- 2-way
- free-flow execution
- body and internal parts in stainless steel

900



- DN 15 ~ 100
- all connections possible
- 2-way or 3-way
- body and internal parts in 316L

2000



- Low Noise control valves
- pressure balanced control valves
- 2-way or 3-way

3000



- DN 4 ~ 25
- DIN PN 10-100
ANSI 150/300/600
- 2-way or 3-way
- body in 316L
- high temperature executions
- cryogenic executions
- bellows seal control valves

Bellow



- double and triple walled
- according to TA-Luft
- safety packing set
- leak detection connection

High temperature



- high temperature stem extension
- special packings
- available in series 800 / 2000 / 3000
- available with bellows seal

Cryogenic



- available in series 800 / 2000 / 3000
- up to -200 °C
- 2-way or 3-way
- special packings
- optional: fully stainless steel actuators